


VIDEO COLONOSCOPE

New Tactile Insertion Tube (TIT) Technology








LED At Tip

HD Imaging



TIT

Auxiliary Channel



Single Step, Water Proof Connector

Features:

- Super Bright LED-At-Tip: Experience 30% more Brightness & 15% wider spread thanks to the new phosphor coating on the LED substrate, supporting high reliability over years of use.
- Ottomed patented LED-At-Tip technology does away with the fragile light guide glass fibre bundle making the scopes very sturdy and environment friendly. Long life, superior light intensity, low maintenance & low replacement cost.
- HD Imaging.
- A new tactile insertion tube (TIT) construction which is 1:1 torque sensitive. Quick Torque Transmission (QTT) technology allows rapid control of the scope helping the user to carry out minimally invasive, precise and effective procedures.
- Dedicated auxiliary water channel washing the mucosa of the lower GI tract.
- Ultra light weight, single step waterproof connector makes endoscope more reliable & User-friendly.









anufacturer

Specifications:

| Model | OVC-2H (L/I/S) | | |
|----------------------------|--|------------------------------|--|
| Optical System | Field Of View | 140° | |
| | Direction Of View | Forward Viewing | |
| | Depth Of Field | 3-100 mm | |
| | Optical Technology - mBLU | mBLU Mode 1 | |
| Insertion Tube | Distal End Outer Diameter | 13 mm | |
| | Insertion Tube Outer Diameter | 12.8mm | |
| | | 1. Air/water nozzle | |
| | | 2. Illumination LEDs (W) | |
| | Distal End Enlarged | 3. Objective lens | |
| | | 4. Instrument channel outlet | |
| | | 5. Auxiliary water channel | |
| | Working Length | L: 1680 mm | |
| | | l : 1330 mm | |
| | | S: 730 mm | |
| Instrument Channel | Channel inner diameter | 3.7 mm | |
| | Minimum visible distance | 3 mm from the distal end | |
| | Direction from which endo-therapy accessories enter and exit the endoscopic image | | |
| Air Flow Rate | | 25 cm∛s | |
| Bending Section | Angulation Image | UP 180° | |
| | | DOWN 180° | |
| | | RIGHT 160° | |
| | | LEFT 160° | |
| Total Length | | L: 1980 mm | |
| iotat Length | | l : 1630 mm | |
| | | S: 1030 mm | |
| Compatible Video Processor | | OVP-SEII Plus, OVP-SEII | |



Available at:

Xavier Med Pvt. Ltd. 1-10-51/2, Road 6B, Dwarakapuram,

Dilsukhnagar, Hyderabad - 500060 www.buyxavier.com Customer Care: 8008895680,

Service: 8008895079